LATEX SEALANTS

XtraBond®25
Acrylic Latex Sealant

XtraBond®25 is a premium grade multi-purpose acrylic latex sealant formulated to provide excellent adhesion and durability to a wide variety of interior and exterior substrates and applications. XtraBond®25 has been specially developed for the installation of windows and doors.

XtraBond®50
Siliconized Acrylic Latex Sealant

XtraBond® 50 is a premium grade multi-purpose siliconized acrylic latex sealant. Manufactured and developed to provide excellent adhesion to vinyl, aluminum, wood, sheet metal and most common building materials without the need of a primer. It has been specially developed for the use in the installation of windows & doors and has minimal shrinkage. XtraBond® 50 cures rapidly to form a durable tight bond.

XtraBond®50S
Sanded Premium Grade Siliconized Latex Sealant

XtraBond®50S is a Premium siliconized acrylic sanded color caulk used for caulking and sealing corners, edges and joints in tile, counters or granite surfaces. Use XtraBond®50S caulking countertops and around sinks, bathtubs and backsplashes. Meets ASTM C834 standards for exterior grade caulks.

XtraBond®100
Acrylic Urethane Sealant

XtraBond®100 is a premium grade acrylic urethane sealant. It has been specially developed for the use in the installation of windows, doors and siding markets. XtraBond®100 is mildew resistant and has been formulated to provide minimal shrinkage when cured. XtraBond®100 cures rapidly to form a durable tight bond

XtraPatch™75
Textured Patch Sealant

XtraPatch™75 s a textured, gun grade, acrylic urethane latex patch sealant used for sealing and patching exteriors surfaces. Specially formulated for substrates such as Stucco, Concrete, Masonry and Block Walls. It has excellent adhesion to wood, metal, plastic or glass. XtraPatch™ 75 will not sag, stain or discolor over time.

SILICONE SEALANTS

XtraBond®150
Premium Grade Silicone Sealant

XtraBond®150 is a one component, permanently flexible, RTV Mildew resistant silicone sealant. Manufactured for excellent adhesion to cultured marble, tile, glass, vinyl, aluminum, and sheet metal without the need of a primer. XtraBond®150 cures rapidly when exposed to atmospheric moisture to form a durable tight bond.

XtraBond®150HT
High Temp Silicone

XtraBond®150HT is a one part, easy to use, non slumping paste that cures to a silicone rubber when exposed to atmospheric moisture at room temperature. This product is formulated to perform at temperatures ranging from -80 deg. F to 500 deg. F continuous, and up to 600 deg. F for intermittent exposures.

XtraBond®250
Premium Grade Silicone Sealant

XtraBond®250 is a mildew resistant, acetoxy-based high performance silicone designed for many applications. It is formulated as a one component, permanently flexible, silicone and offers excellent adhesion. It is recommended for high moisture areas such as kitchens, baths, and walk-in coolers.

XtraBond®350
Low Modulus Neutral Cure Silicone

XtraBond®350 is a one component, low modulus, 100% high performance alkoxy cure silicone sealant that cures in atmospheric moisture. Manufactured for excellent adhesion to vinyl, glass, aluminum, wood, sheet metal and most common building materials without the need of a primer. XtraBond®350 cures rapidly to form a durable tight bond.

XtraBond®450
Premium Grade Silicone Sealant

XtraBond®450 is a one component, non-sag, permanently flexible neutral cure silicone sealant. Manufactured for excellent adhesion to vinyl, glass, aluminum, wood, sheet metal and most common building materials without the need of a primer. XtraBond®450 cures rapidly when exposed to atmospheric moisture to form a durable tight bond.

HYBRID POLYURETHANES

XtraBond®9500
Hybrid Polyurethane Sealant

XtraBond® 9500 is a high performance, one component, permanently flexible, easy to use, multi-purpose fast cure modified polyurethane sealant. XtraBond® 9500 cures rapidly when exposed to atmospheric moisture to form a durable bond.

XtraBond®9500UC
Hybrid Polyurethane Sealant

XtraBond®9500UC is a high performance, one component, permanently flexible, easy to use, multi-purpose fast cure modified polyurethane sealant. XtraBond®9500UC cures rapidly when exposed to atmospheric moisture to form a durable bond.

XtraBond®9500TX
Hybrid Polyurethane Sealant

XtraBond®9500TX is a textured high performance, one component, permanently flexible, easy to use, multi-purpose fast cure modified polyurethane sealant. XtraBond®9500TX cures rapidly when exposed to atmospheric moisture to form a durable bond.

XtraBond®9500M
Hybrid Polyurethane Sealant

XtraBond®9500M is a highly flexible, gun grade, advanced polymer mirror adhesive. Specially formulated for bonding large and small mirrors to substrates such as dry wall, wood & metals. It has excellent adhesion to all coated mirror backings including plate glass and acrylics. Xtrabond®9500M has been designed with high flex, to address uneven walls.

XtraBond®9500SL
Hybrid Polyurethane Sealant

XtraBond®9500SL is a high performance, self-leveling, one component, permanently flexible, easy to use, multi-purpose fast cure modified polyurethane sealant. XtraBond®9500 cures rapidly when exposed to atmospheric moisture to form a durable bond.

XtraBond®9500SC
Hybrid Polyurethane Sealant

XtraBond®9500SC is a high performance, one component, easy to apply surface coating. XtraBond®9500SC is approved for moisture driven markets and the product has been specifically designed for the truck, trailer and container markets to assure a waterproof surface coat & patch.

FOAMS

XtraFoam®
Miniminal Expanding Foam Sealant

XtraFoam® is a very low expanding, one-component, multipurpose, polyurethane foam specially formulated to seal around window and door frames. The low pressure, airtight insulation foam blocks drafts, moisture and insects without bowing the window. It is environmentally safe, contains no CFC's or HCFC's.

XtraFoam®CC
Climate Control Winter Grade Foam

XtraFoam®CC is a very low expanding, one-component, multipurpose, polyurethane foam specially formulated to be applied in severe climate conditions. Its formulation can be used at temperatures as low as 10 Degrees F. The low pressure, airtight insulation foam blocks drafts, moisture and insects. It is environmentally safe, contains no CFC's or HCFC's.

XtraFoam®MB
Multi-bond Adhesive Foam

XtraFoam®MB is a multiple purpose one component gun grade foam. It is specially designed for subfloor, marble, drywall, insulation panels and metals. It has extremely low post expansion and adheres well to all building materials such as wood, concrete, brick, marble, granite.

XtraFoam®HH
Hand held Adhesive Foam

A very low expanding, one-component, multipurpose, polyurethane foam specially formulated to seal around window,doors, insulation areas and where air infiltration occurs. The low pressure, airtight insulation foam blocks drafts, moisture and insects without bowing the windows. It is environmentally safe, contains no CFC's or HCFC's.

XtraFoam®Black
Minimal Expanding Black Foam Sealant

XtraFoam®Black is a very low expanding, one-component, multipurpose, polyurethane foam specially formulated to blend in and seal around voids for the RV industry, transportation industry, HVAC and Automotive industry. The low pressure, airtight insulation foam blocks drafts, moisture and insects without bowing the joints. It is environmentally safe, contains no CFC's or HCFC's and does not require painting when used in the above application..

POLYURETHANES

XtraBond®7500
Fast Curing Polyurethane Sealant

XtraBond® 7500 is a one component, high performance, permanently flexible, easy to use, multi-purpose fast cure polyurethane sealant. XtraBond® 7500 cures rapidly when exposed to atmospheric moisture to form a durable bond.

XtraBond®8500
Modified Polyurethane Sealant

XtraBond® 8500 is a one component, medium modulus, permanently flexible, multi-purpose easy to use fast cure modified polyurethane sealant. XtraBond® 8500 is environmentally friendly and offers excellent adhesion to vinyl, sheet metal, steel, pre-painted metals, wood, glass, aluminum, plastic, common construction substrates of: window, door, siding, flashing & underlayment papers.

CO-POLYMER

XtraBond®2500
Co-Polymer Sealant & Adhesive

XtraBond® 2500 is a single component, permanently flexible, high performance adhesive/sealant. Manufactured for excellent adhesion and performance to a wide variety of roofing substrates, tile, concrete, clay, slate, pre-painted metals, masonry, stone, aluminum, and sheet metal without the need of a primer. XtraBond® 2500 cures rapidly when exposed to atmospheric moisture to form a durable tight bond.

BUTYL

XtraBond®1500
Premium Grade Butyl Rubber Sealant

XtraBond® 1500 is a one component, gun grade, permanently flexible, general purpose butyl rubber sealant. Manufactured for excellent adhesion to glass, wood, roof tile, concrete, clay, slate, sheet metal, most common building materials and most plastics without the need of a primer. XtraBond® 1500 has excellent weatherability, non staining, paintable and stays permanently elastic even when exposed to both high and low temperatures.

TAPES

Butyl Tape
Cross Linked Butyl Backed Tape

A Premium Grade Multi-Purpose Cross Linked Butyl Based Tape. It is manufactured in convenient ready to use tapes, beads, and handy rolls. The material is comprised of a soft and pliable butyl and is easily worked by hand, yet bonds instantly to a wide variety of substrates.



XtraTape GT950
Closed Cell Polyolefin Foam Tape

Premier GT950 Series Glazing tapes are closed cell polyolefin foam tapes specifically designed for the fenestration and OEM industry. The tape is coated with a solvent based acrylic adhesive on both sides. The unique tape seals against air, moisture, dust and any outside penetration. Both sides provide optimum performance and is developed to withstand high UV exposure. All of our tapes are in accordance and complies to AAMA 810.1-92 Type 1.

FIRE STOP

XtraStop™550
Smoke & Draft Sealant

XtraStop™ 550 is designed for filling areas around wires, vents, pipes, ducts and other wall penetrations & construction voids. It is a commercial quality, intumescent, non combustible fire, smoke and draft stopping sealant. XtraStop™ 550 is a water based sealant and can be used wherever ASTM E-814 Specification is needed. The Fire Stop Caulk can withstand 3000 degrees for up to 8 hours and can be safely removed with soap and water prior to curing.

Eco-Friendly Fact

Not only do the products listed here follow a "green" standard, we at Premier Industrial Supply go beyond the obvious. For instance, the plastic cartridges that our sealants and adhesives are filled in are made with post-recycled product, and we encourage our customers to follow a "recycling" program.

TOLL-FREE **866.512.GLUE** (4583)

WWW.PREMIERINDUSTRIAL.NET