

XTRABOND®9500UC

ULTRA-CLEAR MODIFIED POLYURETHANE SEALANT

XtraBond®9500UC is a high performance, one component, permanently flexible, easy to use, multi-purpose fast cure modified polyurethane sealant. XtraBond®9500UC cures rapidly when exposed to atmospheric moisture to form a durable bond.

FEATURES

- Advanced Clear Formulation
- Environmentally friendly
- No solvents, very low VOCs
- Extrudes at zero degrees
- Aggressive Adhesion to common construction substrates

APPLICATIONS

- Perimeter sealing of windows, doors & skylights
- Sheet Metal
- Industrial Applications
- Construction Flashing Applications

SPECIFICATIONS

Skin Time	Less than 20 minutes @ 77 degF / 50% RH
Tack Free Time	Less than 1 hour @ 77 degF / 50% RH
Cure Rate	1/4" Bead per 24 Hrs
VOC.....	9 g/L (0.0751 lb/gal)
Elongation @ Break	450% - 500%
Shore A	30
Movement Capability % ..	25%
UV Rating	No discoloration or change in appearance after 2500 hours of UV
Lap Shear	175 psi
Tensile Strength	200 psi
Staining	None
Low Temp. Flexibility	Retained to -90 degrees
High Temp. Flexibility	Up to 425 F for short periods
Sag	None



Proud Member

TOLL-FREE

866-512-GLUE (4583)

WWW.PREMIERINDUSTRIAL.NET



XTRABOND® 9500UC

ULTRA-CLEAR MODIFIED POLYURETHANE SEALANT

HOW TO USE:

For best results, prepare clean, dry surface. Cut nozzle to desired bead size and puncture inner seal. Apply with a caulking gun forcing sealant onto the substrate, then tool if needed. Can be painted within 2 hours depending upon bead size. Clean excess material with mineral spirits or similar solvents. It is the user's responsibility to thoroughly test any proposed uses with any and/or all substrates.

SURFACE PREPARATIONS:


The substrate must be clean, dry, frost free, sound and free of any oils, greases or incompatible sealers, paints or coatings that may interfere with adhesion. Do not apply if surface is damp or contaminated. It is recommended to test all substrates prior to applications.

COLORS:

Ultra Clear.

PACKAGING:

- 10.1 fl oz plastic fixed or twist-on nozzle cartridges
- 10.3 oz & 20 oz fl oz. Sausages
- 1, 3, 5 & 55 gallon available upon request.



STORAGE LIFE:

10 months shelf life. Material is to be stored in a controlled environment below 75 degrees

SPECIFICATIONS:

Exceeds the requirements of ASTM C 920, Type S, Grade NS, Class 25, Use NT, M, G and A • Federal Specification TT-S-00230C, Type II, Class A • CAN/CGSB-19 13-M87 • AAMA 808.3-92 Exterior Perimeter Sealing.

RECYCLE, PLEASE

Premier Industrial Supply, Inc. is committed to caring for the environment and adheres to nationally recognized standards for "green" manufacturer. Our product meets VOC emission standards, and our tubes are made with post-recycled plastic material. We ask that you do your part and recycle the empty cartridges when done.

LIMITED LIFETIME WARRANTY

This product is guaranteed to give satisfactory performance if applied in accordance with the label directions. Liability to Premier Industrial Supply, Inc. (Premier) is limited to a full refund of the purchase price or product replacement if product is proven defective. Premier shall not be liable for loss or damage, whether direct, consequential or incidental. There are no other warranties expressed or implied including the implied warranty of merchantability or fitness for a particular purpose.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



EMAIL & ONLINE:
INFO@PREMIERINDUSTRIAL.NET
WWW.PREMIERINDUSTRIAL.NET

WEST COAST:
23040 N 11TH AVE. STE 112
PHOENIX, AZ 85027
PH: 623-780-3160
FX: 623-478-2566

EAST COAST:
4282B STRAUSSER ST. NW
NORTH CANTON, OH 44720
PH: 330-244-2907
FX: 330-244-9423

SPECIFICATIONS SUBJECT TO
CHANGE WITHOUT NOTICE